



Skeleton Gun for 310ml Tubes

Product SKU:	3005018
Material:	Adhesive
Colour:	Translucent
Weight:	0.4Kg
Operating Temperature Range:	-40°C to 200°C

Key Features:

Premium Silicone Formula: Our silicone lubricant spray offers superior performance, effectively reducing friction and enhancing movement for various applications.

Moisture Resistant: Provides a protective barrier against moisture, preventing rust and corrosion on metal surfaces.

Non-Staining and Clear: The clear formula ensures no unsightly

stains are left behind, making it ideal for both household and industrial use.

Multi-Purpose: Perfect for lubricating a wide range of surfaces, including metal, plastic, and rubber, ensuring long-lasting protection and improved functionality.

Easy Application: The convenient spray nozzle allows for precise application, ensuring you can reach tight spaces with ease.

Applications:

Door and Window Tracks: Helps doors and windows slide more easily by lubricating the tracks and preventing sticking or squeaking.

Automotive Maintenance: Used on hinges, locks, and rubber seals to prevent rust, squeaks, and wear, ensuring smooth operation.

Tools and Equipment: Lubricates and protects moving parts of tools, machinery, and appliances, extending their lifespan and preventing corrosion.

Conveyor Systems: Applied to rollers and belts in industrial conveyors to reduce friction and improve efficiency.

Bicycle Maintenance: Used on gears, chains, and brakes to reduce friction and improve performance, while also preventing rusting.

Electrical Connections: Prevents moisture buildup and corrosion in electrical connections and terminals, ensuring reliable performance.

Plastic and Rubber Parts: Lubricates and protects plastic or rubber components, reducing wear and tear and preventing cracking or sticking.

Hoses and Cables: Reduces friction on hoses and cables, making them easier to manage and improving their lifespan.

Although the technical details and recommendations made correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use Polymax products must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product.

All sales subject to our standard terms www.polymax.co.uk/sales-terms