

MAPEI G19 Two part PU Adhesive 2kgs



Product SKU:	3005005
Material:	Polyurethane (PU)
Colour:	Beige
Operating Temperature Range:	-40°C to 100°C

Mapei G19 is a premium, epoxy-based grout that offers exceptional adhesion, durability, and stain resistance, making it ideal for both residential and commercial projects. Its versatile applications include tile grouting in wet areas, high-traffic locations, and industrial settings, all while providing a seamless beige finish that complements various tile designs.

Key Features:

Mapei G19 is a high-performance, epoxy-based grout that stands out for its exceptional adhesive properties and resistance to staining. This versatile grout is perfect for both residential and commercial projects, ensuring a polished finish that enhances the aesthetic appeal of any tiled surface. Key benefits include:

Superior Adhesion: Mapei G19's strong bonding capabilities ensure that tiles remain securely in place.

Stain Resistance: Its unique formulation resists staining and discolouration, making it ideal for areas prone to spills.

Durability: Designed to withstand chemical and mechanical wear, Mapei G19 is perfect for high-traffic areas, offering long-lasting performance.

Water-Resistant: With excellent water-resistant properties, this grout is suitable for wet areas like bathrooms.

Applications:

Tile Grouting: Ideal for grouting ceramic, porcelain, and natural stone tiles on floors, walls, and ceilings, Mapei G19 provides a seamless finish in any setting.

Wet Areas: Perfectly suited for moist environments such as bathrooms, kitchens, swimming pools, and shower areas, offering robust water-resistant performance.

Industrial Applications: Designed for industrial settings where resistance to chemicals, oils, and stains is critical, Mapei G19 excels in factories and food processing areas.

Exterior Installations: This grout is ideal for outdoor applications, ensuring strong weatherproofing capabilities for terraces, balconies, and facades.

Expansion Joints: Mapei G19 is frequently used in areas experiencing temperature fluctuations or vibrations, ensuring stable and reliable grout performance.

Although the technical details and recommendations made correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use Polymax products must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product.
All sales subject to our standard terms www.polymax.co.uk/sales-terms