

Mapei Eco Prime T 5kg



Product SKU:	3005022
Colour:	White
Weight:	5 Kg
Operating Temperature Range:	5°C to 35°C

Revolutionise your flooring and tiling projects with our premium White Surface Primer, designed for exceptional adhesion on various substrates. Ideal for both interior and exterior applications, it provides a reliable foundation for long-lasting results and enhances the performance of your adhesives and finishes.

Key Features:

Discover our premium White Surface Primer, designed to revolutionise your flooring and tiling projects. This versatile primer offers exceptional adhesion properties, making it an essential component for achieving a flawless finish. Its unique formulation ensures excellent compatibility with various substrates, including concrete, cementitious screeds, and anhydrite screeds. The White Surface Primer dries quickly, allowing for swift project progression while enhancing the performance of your chosen adhesives and finishes.

Whether you're working on new installations or renovations, this primer provides a reliable foundation that optimises the bond between surfaces and finishes, ensuring long-lasting results. Its waterproofing capabilities further enhance its functionality, making it an ideal choice for both interior and exterior applications.

Applications:

Surface Preparation: Ideal for preparing substrates such as concrete, cementitious screeds, and anhydrite screeds before applying adhesive, flooring, or other finishes.

Bonding Agent: Enhances the adhesion of self-leveling compounds, adhesives, and tiles to challenging substrates, including non-absorbent or smooth surfaces.

Waterproofing: Can be used as a bonding layer for waterproofing membranes or coatings.

Underfloor Heating Systems: Suitable for priming subfloors before the installation of underfloor heating systems.

Renovations: Used for priming old, worn-out surfaces to improve the bond between the new finish and the substrate.

Interior and Exterior Applications: Suitable for both interior and exterior applications to improve surface performance before flooring or tiling.

Although the technical details and recommendations made correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use Polymax products must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product.
All sales subject to our standard terms www.polymax.co.uk/sales-terms