



Mapesil AC 113 Silicone Sealant 310ml

Product SKU:	3043662
Colour:	Cement Grey
weight:	0.39 Kg

Mapei Mapesil AC 113 Silicone Sealant is a high-performance, neutral cure sealant that offers superior adhesion, flexibility, and long-lasting durability, perfect for both residential and commercial applications. Ideal for sealing joints, waterproofing, bonding glass and metal, and more, it provides excellent resistance to moisture, UV, and temperature fluctuations, with a discreet cement grey finish.

Key Features:

Mapei Mapesil AC 113 Silicone Sealant is a high-performance, neutral cure silicone sealant that offers superior adhesion, flexibility, and long-lasting durability. Designed to withstand moisture, UV rays, and temperature fluctuations, this versatile sealant is perfect for both residential and commercial applications. Its fast curing time and ease of use make it the go-to solution for professionals and DIY enthusiasts alike. The cement grey colour provides a discreet and professional finish, making it suitable for a wide range of projects.

Applications:

Joint Sealing: Perfect for sealing expansion joints and gaps in both interior and exterior areas, including around windows, doors, and wall junctions.

Tile and Stone Applications: Ideal for sealing joints between tiles, stone surfaces, and along grout lines in bathrooms, kitchens, and other wet areas.

Waterproofing: Excellent for sealing areas exposed to water, such as around bathtubs, showers, sinks, and other plumbing fixtures, ensuring a watertight seal.

Glass and Metal Bonding: Highly effective for sealing and bonding glass, metal, and plastic materials in both construction and industrial applications.

Structural Sealing: Suitable for sealing joints in construction projects where movement or vibration may occur, such as in facades, curtain walls, and partitions.

Weatherproofing: Ideal for outdoor use to seal gaps and joints on external structures, providing protection against rain, wind, and environmental factors.

Although the technical details and recommendations made correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use Polymax products must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product.
All sales subject to our standard terms www.polymax.co.uk/sales-terms