

Product : Standard Mirror with Rigid Pole



The Standard Mirror with Rigid Pole is a durable, lightweight visibility and inspection solution designed for both traffic safety and industrial applications. Manufactured from high-quality materials, it delivers excellent optical performance, long-term weather resistance, and reliable operation in demanding environments.

Key Benefits:

High-Quality Construction - Features a reflective acrylic mirror surface for clear visibility and image quality.

UV-Resistant Design - Maintains appearance and performance even after prolonged outdoor use.

Lightweight and Robust - Easy to install, transport, and reposition when required.

Vandal-Resistant Options - Available with anti-shock reflective material for locations exposed to frequent vandalism or accidental impacts.

Versatile Installation Options – Can be mounted on a pole or wall.

Multiple Sizes – Different sizes options available for every application.

Applications:

Traffic and Road Safety – Improves visibility at junctions, blind spots, exits, and driveways.

Warehouse and Industrial Safety – Improves visibility on aisles, loading bays and forklift routes.

Retail security and loss prevention – Improves visibility in stores and stockrooms

Vehicle Security and Inspections Operations – Under vehicle inspections, at checkpoints and security points.

Facility and Infrastructure – Routine maintenance and inspection of in-situ equipment

Mechanical and Industrial Maintenance – Routine maintenance and inspection of HVAC equipment

Although the technical details and recommendations made correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use Polymax products must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product.

All sales subject to our standard terms www.polymax.co.uk/sales-terms

Technical Data:

SKU	Diameter (mm)	Gross Weight (Kg)
1122302	300	1.40
1122303	400	2.20
1122304	500	2.90
1122305	600	3.60
1122306	700	4.80
1122307	800	6.00
1122308	900	7.60

Visibility Distance:

Distance	Ø300	Ø400	Ø500	Ø600	Ø700	Ø800	Ø900
4 m	*	*	*	*	*	*	*
5 m	*	*	*	*	*	*	*
6 m		*	*	*	*	*	*
7 m			*	*	*	*	*
8 m				*	*	*	*
9 m					*	*	*
10 m							*
11 m							*
12 m							*

Although the technical details and recommendations made correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use Polymax products must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product.
 All sales subject to our standard terms www.polymax.co.uk/sales-terms